REACH ROBOTICS

RB-3XXX

BRAVO 3

3-FUNCTION MANIPULATOR

A Tough, 3-Function Manipulator for Small Under Water Vehicles.

LIGHTWEIGHT & COMPACT
Small footprint for easy integration

RELIABLE PERFORMANCE
Engineered for tough underwater conditions

FIELD SERVICEABLE
Quick maintenance with replaceable components

EASY TO INTEGRATE
Simple mechanical and electrical interfaces

Lift Capacity	Reach	Functions	In-Air Weight	Depth Rating
15 kg / 33 lb	**360 mm / 14.2 in**	**3**	**4 kg / 9 lb**	**450 MSW / 1480 ft**

TECHNICAL DRAWINGS







JOINT ROTATION	
A	86.5mm
B	360° (continuous)
C	180°

COMPONENT DIMENSIONS	
A	264mm
B	150mm
C	138mm

RANGE OF MOTION	
A	R372mm
B	330mm

END EFFECTOR OPTIONS

CUTTER JAWS
RB-1042

END-EFFECTOR INTERFACE
RB-1054

PARALLEL JAWS
RB-1034

QUAD JAWS
RB-1041

WIDE QUAD JAWS
RB-1025

KEY FEATURES

- All-Electric.
- 3-Functions for Precise Manipulation.
- Designed and Tested for Harsh Environments.
- Intuitive User Interface with 3D Visualisation and Telemetry.
- Software Developer Kit (SDK) for Custom Control Applications.

MOUNTING KITS

REACH BRAVO FALCON INTEGRATION KIT
Seamless integration kit for the Saab Seaeye Falcon ROV

CONTROLLER OPTIONS

You can use our Software Development Kit (SDK), available with the purchase of a manipulator, or map movements to your existing ROV controller. For more information, contact sales@reachrobotics.com.

ACCESSORIES

REACH BRAVO IP WRIST CAMERA
A wrist camera for Reach Bravo manipulators

REACH BRAVO VACUUM PULLING KIT
Maintain and Monitor

SPECIFICATIONS	REACH BRAVO 7	REACH BRAVO 5	REACH BRAVO 3	REACH BRAVO 2
Functions	7	5	3	2
Reach	900 mm / 33.5 in	700 mm / 27.6 in	360 mm / 14.2 in	270 mm / 10.6 in
Wrist Rotation Torque	20 Nm / 177 lb-in	20 Nm / 177 lb-in	20 Nm / 177 lb-in	20 Nm / 177 lb-in
Wrist Rotation Speed	68° / s	68° / s	68° / s	68° / s
Grab Speed	3 s	3 s	3 s	3 s
Grab Force	80 kg / 44 lb	80 kg / 44 lb	80 kg / 44 lb	80 kg / 44 lb
Lift Capacity	10 kg / 22 lb	12 kg / 26 lb	15 kg / 33 lb	N/A
Weight (Air)	9.5 kg / 21 lb	7.5 kg / 16.5 lb	4 kg / 9 lb	2.8 kg / 6 lb
Weight (Water)	4.5 kg / 10 lb	4 kg / 9 lb	2.6 kg / 5.7 lb	1.6 kg / 3.5 lb
Outer Diameter	92 mm / 3.6 in	92 mm / 3.6 in	82 mm / 3.2 in	82 mm / 3.2 in
Connector Cable	8 Pin Subconn (Communications), 4 Pin Subconn (Power)	8 Pin Subconn (Communications), 4 Pin Subconn (Power)	13 Pin Ethernet Subconn (DBH13M)	13 Pin Ethernet Subcon (DBH13M)
Control Modes	Position, Velocity, Cartesian Velocity (X, Y, Z, R, P, Y)	Position, Velocity, Cartesian Velocity (X, Y, Z)	Position, Velocity	Position, Velocity
Voltage	24 - 48 V	24 - 48 V	24 - 48 V	24 - 48 V
Power (Nominal)	400 W	200 W	100 W	75 W
COMS	Serial (232 / 485) AND Ethernet	Serial (232 / 485) AND Ethernet	Serial (232 / 485) AND Ethernet	Serial (232 / 485) AND Ethernet
Rated Depth	450 MSW / 1480 ft	450 MSW / 1480 ft	450 MSW / 1480 ft	450 MSW / 1480 ft
Rated Temp	5 - 35 °C / 41 - 95 °F	5 - 35 °C / 41 - 95 °F	5 - 35 °C / 41 - 95 °F	5 - 35 °C / 41 - 95 °F
Storage Temp	-10 - 80 °C / 14 - 176 °F	-10 - 80 °C / 14 - 176 °F	-10 - 80 °C / 14 - 176 °F	-10 - 80 °C / 14 - 176 °F