# **BRAVO ROTATING CUTTER**

A Tough, 2-Function Manipulator for Inspection Class Vehicles

The Bravo Rotating Cutter is comprised of the Bravo 2-funtion manipulator (RB-2130) with cutter endeffector attached (RB-1042).



- DEXTEROUS 2-Function (or custom fit) Highly Modular & Configurable
- RUGGED 450m Depth Rating 2kN Axial Load
- SMART In-Built Kinematics Master Arm Controlled



ROV & UGV Proven •

## **NEW MK2 FEATURES**

- Slip-rings in all inlines •
- Increased 450m depth rating (600m rated in the future) •
- High strength linear (approx. up to 10kN) •
- Higher joint speed •
- Increased reliability & easier maintenance

#### **FEATURES**

- Ready-built and designed for industry leading inspection-• class vehicles
- All-Electric, Zero Oil
- End effectors: grabbers, probe handlers, cutters (or BYO) •
- Advanced software interface with 3D visualisation •
- Adjustable grab force pick up a sea urchin or cut a cable •
- Quick to integrate •

# STRONG GRIP, CLEAN CUT

The Bravo Rotating Cutter is essential for intervention missions requiring force and precision. This configuration combines the manipulators powerful linear and continuous rotatory actuator, with the end effectors ability to sever softline, copper and electrical cable up to 25mm diameter, resulting in a powerful tool for inspection-class ROVs.

ELECTRICAL

Voltage Nominal Power COMS

Material

24-48V 60W RS232/RS485/Ethernet

ENVIRONMENTAL Depth 450MSW Temp

0°C to 40°C AL7075 T6

MECHANICAL • Weight (Air) 2800g Weight (Water) 1600g

Note: Master Arm not included

Master Arm Controller Enabled

Mission Specific End-Effectors | Interchange With Ease















RB-1025

RB-1055

RB-1041

RB-1043

RB-1044 SS


RB-1042

RB-1034




### **SPECIFICATIONS**

Wrist Torque	20Nm	
Axial Load Rating	2kN	
Rotate Speed	45°/s nominal	
Rotate Accuracy	0.1°	
Linear Force	10kN	
Jaw Clamp Force	80kg (800N)	
Outer Diameter	81.6mm	
Connector cable	13 Pin Ethernet Subcon (DBH13M)	
Control Options	Space Mouse, Software GUI, Topside Master Arm	
Control Modes	Position, Velocity	



### Integration Made Easy

Integrate Reach Bravo manipulators with our mounting unit, designed for simple installation on industry leading vehicles. A screw collar system lets you mount and unmount in seconds.







Note: Mount not included

A Revolution for Subsea Inspection & Intervention



Responsive Integration Support



Responsive Remote Support

<u> </u>	۴	۴	ዮ

12 Month Warranty



1000+ Hours Logged



Extended Warranty, Spares Packages & Service Plans Available